


Silenziatore SEB conico in bronzo sferico sinterizzato



Silenziatore conico in bronzo sferico sinterizzato su base esagonale in acciaio ramato



Codice	Articolo	A	Diam	B	C	D	E	H	Ch	Flusso Max	Rumore	Peso
1011	SEB M 5	M5	2,8	4,5	5,5	3,5	4,0	17,0	7,0	4	67	2.2
1012	SEB 1/8	1/8"	7,0	8,5	10,5	4,5	3,8	21,0	12,0	40	81	6
1013	SEB 1/4	1/4"	9,5	11,0	12,5	6,0	4,5	27,0	15,0	65	83	12
1014	SEB 3/8	3/8"	12,0	14,0	17,0	7,0	5,4	35,0	19,0	100	87	22
1015	SEB 1/2	1/2"	15,5	17,0	20,5	8,0	6,0	41,5	23,0	160	90	38
1016	SEB 3/4	3/4"	19,5	21,0	26,5	9,0	7,5	54,0	30,0	220 a 4 bar	92 a 4 bar	80
1017	SEB 1	1"	26,0	26,5	33,0	11,0	9,0	66,0	36,0	350 a 4 bar	91 a 4 bar	148

MATERIALE

- Corpo - ottone - CW 614 N UNI EN 12164 CuZn39Pb3
- Filtro - bronzo sint AF 50 DIN 30 910 T2 CuSn10

CARATTERISTICHE TECNICHE

- Fluido: Aria
- Filtrazione: 50
- Pressione di esercizio: 1 MPa 10 bar
- Temperatura di esercizio: -20° C. +150° C.
- Tolleranze: ISO 2768-C

Livello di rumore in dB 6 BAR

1/8	1/4	3/8	1/2	3/4	1
79	78	82	85	94	95

Livello di rumore in dB 4 BAR

1/8	1/4	3/8	1/2	3/4	1
76	75	81	84	90	92

Prove di flusso

